## **TECH DATA SHEET**



## . .

## Swim year-round with the high-performance Platinum Series inverter heat pump!

Engineered with the very latest full DC inverter technology, The Platinum series allows so you can swim all year round with the lowest operating costs.

It's premium features make the Platinum Series a standout, with a stylish metal cabinet, powerful performance, wi-fi control and an intelligent LCD touch screen controller with 4 smart operating modes.


The unique design provides vertical air discharge from the top and bottom of the heat pump, delivering better airflow, higher efficiencies, and space saving installation options.

- Modern Metal Cabinet: durable against harsh weather conditions.
- Intelligent Controller: 4 smart operating modes
- C.O.P of up to 16.5
- Top & bottom air discharge
- Latest DC full inverter technology including compressor, fans & control
- Wi-Fi Control: control your pool heater anywhere, anytime.

		Heating		Heating		Cooling	
Performance		Winte	ər	Si	ummer	mer   7   6   25.0   ·3.38   ~7.4   0/1/50   ·4500   ·4500   ·4500   ·4500   ·57   32   d sheet metal   wired   Reverse Cycle)   K4   ·53   ·25   0   ·25   ·26	Summer
Ambient Air Temp.	°C	15			27		35
Entering Water Temp.	°C	26		26		30	
Heating/Cooling Capacity	kW	4.2~19.9		5.6~25.0		11.7	
Consumed Power	kW	0.53~3.83		0.34~3.38		3.1	
C.O.P.		8.0~5.2		10	6.5~7.4	3.74	
Power Supply		220-240/1/50					
Air Flow	m³/h		3000-4500				
Compressor		Туре		Brand		No.	
Compressor		Rotar	у	Pa	nasonic	ic 1	
Heat Exchanger		Material		Туре		Spiral (Twisted)	
neutexchunger		Titanium		Tub	e in shell		Yes
Fan		No.	Power	Input	Speed	DirectionPMHorizontal	
		1	60	W	400-800 R		
Operating Air Temp.	°C	-15 to 43					
Max. Rated Input Power	kW	4.80					
*Running Current at 100%	А	15.57					
Refrigerant		R32					
Casing Type		Matte-finished sheet metal					
Connection Type			Hardwired				
Defrost	Auto Defrost (Reverse Cycle)						
Moisture Resistance			IPX4				
Noise (1M)	dB(A)		44-53				
Noise (10M)		16-25					
Water Connection	mm	40					
Water Flow Volume	L/min	172					
Water Pressure Drop (max)	kPa	10.5					
Net Weight	kg	140					
Net Dimensions (LxWxH)	mm	1330 x 548 x 930					

\*Running current does not include load of circulation pump.





DEDEODI	AANCE	

mm

